Response to Lior Pachter's "usability" blog post.

Lior Pachter wrote a <u>third blog post</u> on our <u>Network Deconvolution</u> paper. We responded to his first two blog posts at: <u>http://compbio.mit.edu/nd/Response_to_Nonsense_Blog_Post.pdf</u>, and we respond to his third post below.

- (1) Dr. Pachter criticizes our selection of DREAM5 methods in our regulatory network evaluation. Network deconvolution (ND) seeks to eliminate the indirect effects that plague mutual-information (MI) and correlation-based methods. We thus applied ND to the top-performing methods for both MI and correlation. In addition, we applied ND to the top method from each high-performing class of method ('regression', 'meta', and 'other'), even when they were not based on MI or corr. These choices are well justified, as <u>Dr. Pachter's own diagram</u> shows.
- (2) Despite the use of very different parameter settings, Bray and Pachter's results demonstrate that ND consistently improves MI and correlation-based networks, suggesting that ND robustly removes their indirect effects. Bray and Pachter's own plots clearly show this increase in performance for MI and correlation networks, although Dr. Pachter draws the opposite conclusion in his blog post. It is important to note that Bray and Pachter's results were obtained using the parameters of our protein folding application, corresponding to each TF targeting 100% of all genes (which does not happen in real networks). In our paper, we used 10% density for all regulatory networks, corresponding to each TF targeting on average 10% of all genes (consistent with ChIP-Seq data).
- (3) Seemingly surprised by the high performance of ND, Bray and Pachter then decompose the score of the DREAM5 challenge into AUROC and AUPR.
 - AUROC would probably benefit from plotting with a baseline of 0.5 (random), rather than 0. At this scale it seems that all methods perform identically, and that the network inference method makes absolutely no difference, which is not true.
 - In the AUPR plots, differences are more visible, and indeed ND continues to improve on mutual information and correlation-based methods (despite setting alpha=1, beta=0.99 from the protein folding application).
 - We remind Dr. Pachter that we scored all methods using **the exact score used in the DREAM5 challenge** (dating back to 2010), and that the score was not altered in any way.
- (4) From these AUROC and AUPR plots, Dr. Pachter concludes: "Biologically, both results are that the methods cannot reliably predict edges in the network". By "methods" (plural), Dr. Pachter refers to all methods used in the DREAM5 challenge and reflects on the state of network inference research.
 - From Dr. Pachter's 10,000-ft view, it may seem that all methods are equivalent and poorly performing.
 - From the closer view enabled by the DREAM5 network inference challenge:
 - (a) there are differences between methods (methods matter, to quote Dr. Pachter).
 - (b) ND consistently improves upon MI/correlation-based methods for which indirect effects are prevalent.
 - (c) ND also improves on several non-MI/corr-based methods especially at realistic network density values.
- (5) Dr. Pachter then applies ND to all methods in the DREAM5 challenge, <u>using a different threshold</u>, demonstrating that ND indeed **consistently improves the score of all top-performing MI and correlation-based methods**, once more suggesting successful removal of indirect effects. The lack of improvement on the non-MI/correlation networks at the threshold used by Bray and Pachter suggests that **indirect effects are not prevalent in them**.
- (6) Now that Bray and Pachter are more familiar with the DREAM5 challenge evaluations and methods, we encourage them to apply their favorite methods (partial correlation, improvements on ND, or other independent methods) to further improve the state of the art, and publish their results in a peer-reviewed venue.